LORD[®] 7610DTM

Direct-to-Metal Adhesive/Sealant for the Sign Industry

Seal it right the first time! Save time and money with LORD® 7610DTM Direct-to-Metal Adhesive/Sealant.

Features & Benefits:

- · Extended shelf life
- One-component sealer and adhesive
- Seal and adhere directly to unpainted metals
- Easy to apply and tool
- · Paint immediately or within 30 days without surface preparation
- Non-sag
- · Bright white

(ASTM D412)

Part #

3029094

©2022 Parker Hannifin

- Low VOCs/no solvent
- · Chemically resistant when cured
- · Excellent resistance to UV exposure

Technical Data*	
Skin Time, minutes @ 77°F (25°C), 50% RH	15-45
Handling Time, hours @ 77°F (25°C)	6-12
Hardness (Shore A)	50
Tensile Strength, psi (MPa)	200 (1.38) minimum
Lap Shear Strength, psi (MPa)	200-500 (1.38-3.45)
Elongation, %	400 minimum

Cartridge

Size

1/10th Gallon

Case

Qty

12

Weight

8 lbs

Applications

- · General purpose adhesive/sealant
- Seals light leaks
- Gap filling
- Irregular substrates

enir hors de iroduit.

Contact Information:

Engineered Materials Group Cary, NC 27511-7923 USA

phone +1 877 ASK LORD (275-5673)

www.lord.com

Dispensing

Gun

3023577

voc

0.21 lbs/

gallon

Information and specifications subject to change without notice and without liability

therefore. Trademarks used herein are the property of their respective owners.

For a listing of our worldwide locations, visit LORD.com

> 04/22 Rev.6 OD PB8144



ENGINEERING YOUR SUCCESS.

Parker LORD 111 LORD Drive

*Data is typical and not to be used for specification purposes.

Description

LORD 7610DTM

WHT Cartridge