## **LORD®** Urethane Adhesives

for the Sign Industry





Product	Features	Applications	Technical Data*				
			Work Time	Handling Time	Full Cure	Mix Ratio	Color
LORD 7550 A/C Fast	Optically Clear Adhesive for Non-Structural Assemblies UV Resistant Self-leveling	Trimcap Letter Track Aesthetic Assemblies	3-5 minutes	1 hour	72 hours	1:1	Optically Clear
LORD 7542 A/B Medium	Bonds plastics, FRP & SMC with Minimal Surface Prep Odorless Non-flammable	Cross Bonding** Metal to Engineered Plastics for Larger, Outdoor Assemblies	4-7 minutes	1-2 hours	24 hours	1:1	Brown
LORD 7610DTM Slow	Single-Component Easy to Use Bonds to Wide Variety of Materials UV Resistant	General Purpose Adhesive & Seam Sealer Seals Light Leaks Sealer for Channel Letter Cans Water Intrusion Barrier or Sealant	15-45 minutes	6-12 hours	1-5 days	1 Part	Bright White

<sup>\*</sup>Technical data reported at 70-77°F (21-25°C). \*\*Refer to cross bonding chart for specific materials.

	Accessories						
Product	Size	Part #	Dispensing Gun	Mixing Tip	Plunger		
LORD 7550 A/C Fast	50 mL	3003953	3001112	3004476	3009588††		
LORD 7542 A/B Medium	50 mL	3003884	3001112	3004476	3009588††		
LORD 7610DTM Slow	1/10 gal/cart	3029094	3023577	3015312 <sup>†</sup>			

 $^{\dagger}\textsc{One}$  mixing tip ships with dispensing gun.

## **Contact Information:**

Parker LORD Engineered Materials Group 111 LORD Drive Cary, NC 27511-7923 USA

phone +1 877 ASK LORD (275-5673)

www.lord.com

For a listing of our worldwide locations, visit LORD.com

©2022 Parker Hannifin

Information and specifications subject to change without notice and without liability therefore. Trademarks used herein are the property of their respective owners.

OD PB8268

04/22 Rev.1





 $<sup>\</sup>ensuremath{^{\dagger\dagger}}\mbox{Plunger}$  ships with dispensing gun.