

**1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION**

Product name: **LORD 850**  
Product Use/Class: **Acrylic Adhesive, Part 1 of 2**

LORD Corporation  
111 LORD Drive  
Cary, NC 27511-7923 USA

Telephone: 814 868-3180  
Non-Transportation Emergency: 814 763-2345  
Chemtrec 24 Hr Transportation Emergency No.  
800 424-9300 (Outside Continental U.S. 703 527-3887)

**EFFECTIVE DATE:** 10/12/2016

**2. HAZARDS IDENTIFICATION****GHS CLASSIFICATION:**

Flammable liquids Category 2  
Acute toxicity Inhalation - Vapours Category 4 - 43.5% of the mixture consists of ingredient(s) of unknown toxicity.  
Acute toxicity Inhalation - Dust and Mist Category 4 - 44.6% of the mixture consists of ingredient(s) of unknown toxicity.  
Skin corrosion/irritation Category 1B  
Serious eye damage/eye irritation Category 1  
Skin sensitization Category 1  
Respiratory sensitization Category 1  
Reproductive toxicity Category 2  
Specific target organ systemic toxicity (single exposure) Category 3  
Specific target organ systemic toxicity (single exposure) Category 2 Central nervous system  
Specific target organ systemic toxicity (repeated exposure) Category 1 upper respiratory system, Adrenal gland, Kidney, Liver, Nervous system, Central nervous system, Respiratory system  
Hazardous to the aquatic environment - acute hazard Category 3  
Hazardous to the aquatic environment - chronic hazard Category 3

**GHS LABEL ELEMENTS:****Symbol(s)****Signal Word**

DANGER

**Hazard Statements**

Highly flammable liquid and vapor.  
Harmful if inhaled.  
Causes severe skin burns and eye damage.  
Causes serious eye damage.  
May cause an allergic skin reaction.  
May cause allergy or asthma symptoms or breathing difficulties if inhaled.  
Suspected of damaging fertility or the unborn child.  
May cause respiratory irritation.  
May cause drowsiness or dizziness.  
May cause damage to organs.(Central nervous system)  
Causes damage to organs through prolonged or repeated exposure.(upper respiratory system, Adrenal gland, Kidney, Liver, Nervous system, Central nervous system, Respiratory system)

Harmful to aquatic life.  
Harmful to aquatic life with long lasting effects.

### Precautionary Statements

#### Prevention

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.  
Ground/Bond container and receiving equipment.  
Use explosion-proof electrical/ventilating/lighting equipment.  
Use only non-sparking tools.  
Take precautionary measures against static discharge.  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Wear protective gloves/protective clothing/eye protection/face protection.  
Use personal protective equipment as required.  
In case of inadequate ventilation wear respiratory protection.  
Do not breathe dust/fume/gas/mist/vapors/spray.  
Wash thoroughly after handling.  
Do not eat, drink or smoke when using this product.  
Use only outdoors or in a well-ventilated area.  
Contaminated work clothing should not be allowed out of the workplace.  
Avoid release to the environment.

#### Response

In case of fire: refer to section 5 of SDS for extinguishing media.  
Immediately call a POISON CENTER or doctor/physician.  
Specific treatment (see supplemental first aid instructions on this label).  
IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do.  
Continue rinsing.  
IF SWALLOWED: rinse mouth. Do NOT induce vomiting.  
Wash contaminated clothing before reuse.

#### Storage

Store in a well-ventilated place. Keep cool.  
Store in a well-ventilated place. Keep container tightly closed.  
Store locked up.

#### Disposal:

Dispose of contents/container in accordance with waste/disposal laws and regulations of your country or particular locality.

#### Other Hazards:

**This product contains component(s) which have the following warnings; however based on the GHS classification criteria of your country or locale, the product mixture may be outside the respective category(s).**

**Acute:** May cause central nervous system depression characterized by the following progressive steps: headache, dizziness, staggering gait, confusion, unconsciousness or coma. May cause headache and nausea. Harmful if absorbed through skin. Harmful if swallowed. Ingestion is not an expected route of entry in industrial or commercial uses.

**Chronic:** Prolonged or repeated contact may result in dermatitis.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

| <u>Chemical Name</u>         | <u>CAS Number</u> | <u>Range</u> |
|------------------------------|-------------------|--------------|
| Methyl methacrylate          | 80-62-6           | 45 - 50 %    |
| Methacrylate monomer         | PROPRIETARY       | 10 - 15 %    |
| Methacrylate phosphate ester | PROPRIETARY       | 1 - 5 %      |
| Amine curative               | PROPRIETARY       | 1 - 5 %      |
| Amine catalyst               | PROPRIETARY       | 1 - 5 %      |

|                  |             |         |
|------------------|-------------|---------|
| Methacrylic acid | 79-41-4     | 1 - 5 % |
| Paraffin wax     | PROPRIETARY | 1 - 5 % |

Any "PROPRIETARY" component(s) in the above table is considered trade secret, thus the specific chemical and its exact concentration is being withheld.

#### 4. FIRST AID MEASURES

**FIRST AID - EYE CONTACT:** Flush eyes immediately with large amount of water for at least 15 minutes holding eyelids open while flushing. Get prompt medical attention. Immediately flush eyes continuously with lukewarm, gently flowing water for at least 30 minutes. Get prompt medical attention.

**FIRST AID - SKIN CONTACT:** Flush contaminated skin with large amounts of water while removing contaminated clothing. Wash affected skin areas with soap and water. Get medical attention if symptoms occur. Wash clothing before reuse.

**FIRST AID - INHALATION:** Move person to fresh air. Restore and support continued breathing. If breathing is difficult, give oxygen. Get immediate medical attention.

**FIRST AID - INGESTION:** If swallowed, do not induce vomiting. Call a physician or poison control center immediately for further instructions. Never give anything by mouth if victim is rapidly losing consciousness, unconscious or convulsing.

#### 5. FIRE-FIGHTING MEASURES

**SUITABLE EXTINGUISHING MEDIA:** Carbon Dioxide, Dry Chemical, Foam, Water Fog

**UNSUITABLE EXTINGUISHING MEDIA:** Not determined for this product.

**SPECIFIC HAZARDS POSSIBLY ARISING FROM THE CHEMICAL:** Flammable liquid and vapor. Keep containers tightly closed. Isolate from heat, electrical equipment, sparks, open flame, and other sources of ignition. Closed containers may rupture when exposed to extreme heat. Use water spray to keep fire exposed containers cool. During a fire, irritating and/or toxic gases and particulate may be generated by thermal decomposition or combustion.

**SPECIAL PROTECTIVE EQUIPMENT AND PRECAUTIONS FOR FIRE-FIGHTERS:** Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water spray may be ineffective. If water is used, fog nozzles are preferable.

#### 6. ACCIDENTAL RELEASE MEASURES

**PERSONAL PRECAUTIONS, PROTECTIVE EQUIPMENT, AND EMERGENCY PROCEDURES:** Remove all sources of ignition (flame, hot surfaces, and electrical, static or frictional sparks). Avoid breathing vapors. Use self-contained breathing equipment. Avoid contact.

**ENVIRONMENTAL PRECAUTIONS:** Do not contaminate bodies of water, waterways, or ditches, with chemical or used container.

**METHODS AND MATERIALS FOR CONTAINMENT AND CLEANUP:** Keep non-essential personnel a safe distance away from the spill area. Notify appropriate authorities if necessary. Contain and remove with inert absorbent material and non-sparking tools. Avoid contact. Before attempting cleanup, refer to hazard caution information in other sections of the SDS form.

#### 7. HANDLING AND STORAGE

**HANDLING:** Keep closure tight and container upright to prevent leakage. Ground and bond containers when transferring material. Avoid skin and eye contact. Wash thoroughly after handling. Avoid breathing of vapor or spray mists. Do not handle until all safety precautions have been read and understood. Empty containers should not be re-used. Use with adequate ventilation. Because empty containers may retain product residue and flammable vapors, keep away from heat, sparks and flame; do not cut, puncture or weld on or near the empty container. Do not smoke where this product is used or stored.

**STORAGE:** Do not store or use near heat, sparks, or open flame. Store only in well-ventilated areas. Do not puncture, drag, or slide container. Keep container closed when not in use. Refer to OSHA 29CFR Part 1910.106 "Flammable and Combustible Liquids" for specific storage requirements.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### COMPONENT EXPOSURE LIMIT

| Chemical Name                | ACGIH TLV-TWA | ACGIH TLV-STEL | OSHA PEL-TWA         | OSHA PEL-CEILING | Skin |
|------------------------------|---------------|----------------|----------------------|------------------|------|
| Methyl methacrylate          | 50 ppm        | 100 ppm        | 410 mg/m3<br>100 ppm | N.E.             | N.A. |
| Methacrylate monomer         | N.E.          | N.E.           | N.E.                 | N.E.             | N.A. |
| Methacrylate phosphate ester | N.E.          | N.E.           | N.E.                 | N.E.             | N.A. |
| Amine curative               | N.E.          | N.E.           | N.E.                 | N.E.             | N.A. |
| Amine catalyst               | N.E.          | N.E.           | N.E.                 | N.E.             | N.A. |
| Methacrylic acid             | 20 ppm        | N.E.           | N.E.                 | N.E.             | S    |
| Paraffin wax                 | 2 mg/m3       | N.E.           | N.E.                 | N.E.             | N.A. |

N.A. - Not Applicable, N.E. - Not Established, S - Skin Designation

**Engineering controls:** Sufficient ventilation in pattern and volume should be provided in order to maintain air contaminant levels below recommended exposure limits. Caution: Solvent vapors are heavier than air and collect in lower levels of the work area. Sufficient ventilation (using explosion-proof equipment) should be provided to prevent flammable vapor/air mixtures from accumulating.

### PERSONAL PROTECTION MEASURES/EQUIPMENT:

**RESPIRATORY PROTECTION:** Use a NIOSH approved chemical/mechanical filter respirator designed to remove a combination of particulates and organic vapor if occupational limits are exceeded. For emergency situations, confined space use, or other conditions where exposure limits may be greatly exceeded, use an approved air-supplied respirator. For respirator use observe OSHA regulations (29CFR 1910.134) or use in accordance with applicable laws and regulations of your country or particular locality.

**SKIN PROTECTION:** Use neoprene, nitrile, or rubber gloves to prevent skin contact. If contact with the product is prolonged or repeated, Silver Shield or Butyl rubber gloves are recommended.

**EYE PROTECTION:** Use safety eyewear including safety glasses with side shields and chemical goggles where splashing may occur.

**OTHER PROTECTIVE EQUIPMENT:** Use disposable or impervious clothing if work clothing contamination is likely. Remove and wash contaminated clothing before reuse.

**HYGIENIC PRACTICES:** Wash hands before eating, smoking, or using toilet facility. Do not smoke in any chemical handling or storage area. Food or beverages should not be consumed anywhere this product is handled or stored. Wash thoroughly after handling.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

Typical values, not to be used for specification purposes.

|                                   |                        |                               |                              |
|-----------------------------------|------------------------|-------------------------------|------------------------------|
| <b>ODOR:</b>                      | Acrylic                | <b>VAPOR PRESSURE:</b>        | N.D.                         |
| <b>APPEARANCE:</b>                | Amber                  | <b>VAPOR DENSITY:</b>         | Heavier than Air             |
| <b>PHYSICAL STATE:</b>            | Paste                  | <b>LOWER EXPLOSIVE LIMIT:</b> | 1.6 %(V)                     |
| <b>FLASH POINT:</b>               | 59 °F, 15 °C Setaflash | <b>UPPER EXPLOSIVE LIMIT:</b> | 8.8 %(V)                     |
|                                   | Closed Cup             |                               |                              |
| <b>BOILING RANGE:</b>             | N.A.                   | <b>EVAPORATION RATE:</b>      | Faster than n-butyl-acetate. |
| <b>AUTOIGNITION TEMPERATURE:</b>  | N.D.                   | <b>DENSITY:</b>               | 0.97 g/cm3 - 8.11 lb/gal     |
| <b>DECOMPOSITION TEMPERATURE:</b> | N.D.                   | <b>VISCOSITY, DYNAMIC:</b>    | ≥250,000 mPa.s @ 25 °C       |

|   |           |                              |                                     |
|---|-----------|------------------------------|-------------------------------------|
| <b>ODOR THRESHOLD:</b>                        | N.D.      | <b>VISCOSITY, KINEMATIC:</b> | ≥257,732 mm <sup>2</sup> /s @ 25 °C |
| <b>SOLUBILITY IN H<sub>2</sub>O:</b>          | Insoluble | <b>VOLATILE BY WEIGHT:</b>   | 0.03 %                              |
| <b>pH:</b>                                    | N.A.      | <b>VOLATILE BY VOLUME:</b>   | 0.03 %                              |
| <b>FREEZE POINT:</b>                          | N.D.      | <b>VOC CALCULATED:</b>       | 0 lb/gal, 0 g/l                     |
| <b>COEFFICIENT OF WATER/OIL DISTRIBUTION:</b> | N.D.      |                              |                                     |

**LEGEND:** N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

### 10. STABILITY AND REACTIVITY

**HAZARDOUS POLYMERIZATION:** Hazardous polymerization will not occur under normal conditions.

**STABILITY:** Product is stable under normal storage conditions.

**CONDITIONS TO AVOID:** High temperatures. Sources of ignition.

**INCOMPATIBILITY:** Strong acids, bases, and strong oxidizers.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide, carbon dioxide, Ammonia, Oxides of nitrogen, Nitric acid

### 11. TOXICOLOGICAL INFORMATION

**EXPOSURE PATH:** Refer to section 2 of this SDS.

**SYMPTOMS:** Refer to section 2 of this SDS.

**TOXICITY MEASURES:**

| Chemical Name                | LD50/LC50  |
|------------------------------|--|
| Methyl methacrylate          | Oral LD50: Rat 7,900 mg/kg<br>Dermal LD50: Rabbit > 5 g/kg<br>Inhalation LC50: Rat 4632 ppm/4 h GHS LC50 (vapour): Acute toxicity point estimate 11 mg/l   |
| Methacrylate monomer         | N.D.   |
| Methacrylate phosphate ester | Oral LD50: rat > 5,000 mg/kg   |
| Amine curative               | N.D.   |
| Amine catalyst               | Oral LD50: Rat 1,700 mg/kg<br>Dermal LD50: Rabbit 3,200 mg/kg  |
| Methacrylic acid             | Oral LD50: Rat 1,060 mg/kg<br>Dermal LD50: Rabbit 500 - 1,000 mg/kg<br>GHS LC50 (vapour): Acute toxicity point estimate 11 mg/l GHS LC50 (dust and mist): Acute toxicity point estimate 1.5 mg/l |
| Paraffin wax                 | Oral LD50: Rat > 3,750 mg/kg<br>Dermal LD50: Rabbit > 3,600 mg/kg  |

**Germ cell mutagenicity:** No classification proposed

**Carcinogenicity:** No classification proposed

**Reproductive toxicity:** Category 2 - Suspected of damaging fertility or the unborn child.

Components contributing to classification: Methyl methacrylate. Methacrylate monomer. Amine catalyst.

### 12. ECOLOGICAL INFORMATION

**ECOTOXICITY:**

| Chemical Name | Ecotoxicity |
|---------------|-------------|
|---------------|-------------|

|                              |  |
|------------------------------|--|
| Methyl methacrylate          | <u>Fish:</u> Pimephales promelas 243 - 275 mg/196 h flow-through<br>Pimephales promelas 125.5 - 190.7 mg/196 h Static<br>Lepomis macrochirus 170 - 206 mg/196 h flow-through<br>Lepomis macrochirus 153.9 - 341.8 mg/196 h Static<br>Oncorhynchus mykiss > 79 mg/196 h flow-through<br>Oncorhynchus mykiss > 79 mg/196 h Static<br>Poecilia reticulata 326.4 - 426.9 mg/196 h Static<br><u>Invertebrates:</u> Daphnia magna 69 mg/148 h<br><u>Plants:</u> Pseudokirchneriella subcapitata 170 mg/196 h |
| Methacrylate monomer         | N.D.   |
| Methacrylate phosphate ester | N.D.   |
| Amine curative               | N.D.   |
| Amine catalyst               | <u>Fish:</u> Pimephales promelas 1,510 - 1,980 mg/196 h flow-through   |
| Methacrylic acid             | N.D.   |
| Paraffin wax                 | N.D.   |

**PERSISTENCE AND DEGRADABILITY:** Not determined for this product.

**BIOACCUMULATIVE:** Not determined for this product.

**MOBILITY IN SOIL:** Not determined for this product.

**OTHER ADVERSE EFFECTS:** Not determined for this product.

**13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** Disposal should be done in accordance with Federal (40CFR Part 261), state and local environmental control regulations. If waste is determined to be hazardous, use licensed hazardous waste transporter and disposal facility.

**14. TRANSPORT INFORMATION**

**US DOT Road**

**DOT Proper Shipping Name:** Adhesives  
**DOT Hazard Class:** 3  
**SECONDARY HAZARD:** None  
**DOT UN/NA Number:** 1133  
**Packing Group:** II  
**Emergency Response Guide Number:** 128

**IATA Cargo**

**PROPER SHIPPING NAME:** Adhesives  
**DOT Hazard Class:** 3  
**HAZARD CLASS:** None  
**UN-NUMBER:** 1133  
**PACKING GROUP:** II  
**EMS:** 3L

**IMDG**

**PROPER SHIPPING NAME:** Adhesives  
**DOT Hazard Class:** 3  
**HAZARD CLASS:** None  
**UN-NUMBER:** 1133  
**PACKING GROUP:** II  
**EMS:** F-E

The listed transportation classification applies to US DOT Road, IATA Cargo, and IMDG non-bulk shipments. It does not address regulatory variations due to changes in package size, mode of shipment or other regulatory descriptors. For the most accurate shipping information, refer to your transportation/compliance department.

|                                   |
|-----------------------------------|
| <b>15. REGULATORY INFORMATION</b> |
|-----------------------------------|

**U.S. FEDERAL REGULATIONS: AS FOLLOWS:**

**SARA SECTION 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372.:

| <u>Chemical Name</u> | <u>CAS Number</u> | <u>Weight % Less Than</u> |
|----------------------|-------------------|---------------------------|
| Methyl methacrylate  | 80-62-6           | 50.0 %                    |

**TOXIC SUBSTANCES CONTROL ACT:**

**INVENTORY STATUS**

The chemical substances in this product are on the TSCA Section 8 Inventory.

**EXPORT NOTIFICATION**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

NONE

|                              |
|------------------------------|
| <b>16. OTHER INFORMATION</b> |
|------------------------------|

Under HazCom 2012 it is optional to continue using the HMIS rating system. It is important to ensure employees have been trained to recognize the different numeric ratings associated with the HazCom 2012 and HMIS schemes.

**HMIS RATINGS - HEALTH: 2\* FLAMMABILITY: 3 PHYSICAL HAZARD: 1**

\* - Indicates a chronic hazard; see Section 2

**Revision:** Section 2

**Effective Date:** 10/12/2016

|                   |
|-------------------|
| <b>DISCLAIMER</b> |
|-------------------|

The information contained herein is, to the best of our knowledge and belief, accurate. However, since the conditions of handling and use are beyond our control, we make no guarantee of results, and assume no liability for damages incurred by use of this material. It is the responsibility of the user to comply with all applicable federal, state and local laws and regulations.